

Tyre Changer Specifications

Model	Type	Box Size mm	Post Size mm	Turntable Size mm	Assist arm type
TC10	Fixed Post tire changer	800x 390x 500	120x 120x 905	540x 540x 14	Top Assist Arm
TC20	Tilt Post tire changer	840x 390x 500	120x 120x 823	540x 540x 14	Side Assist Arm
TC20A	Tilt Post tire changer	840x 390x 500	120x 120x 823	540x 540x 14	Side Assist Arm
TC30	Tilt Post tire changer	910x 440x 500	120x 120x 863	630x 630x 15	Side Assist Arm

Feature	TC10	TC20	TC20A	TC30
Post	Fixed	Air tilt	Air tilt	Air Tilt
Air jet on jaws			✓	✓
Max rim diam - Internal	12-22"	12-22"	12-22"	12-28"
Max rim diam - External	10-19"	10-19"	10-19"	12-25"
Max rim width	14"	14"	14"	14"
Assist arm style	Top	Side	Side	Side
Tyre inflate	Foot	Foot	Foot	Foot
Head locking style	Manual	Air clamps	Air clamps	Air clamps
Bead breaker	✓	✓	✓	✓
Weight tool	✓	✓	✓	✓
Tyre lever	✓	✓	✓	✓
Pressure gauge	✓	✓	✓	✓
Power supply	240V - 10A	240V - 10A	240V - 10A	240V - 10A
Air supply	8-10bar	8-10bar	8-10bar	8-10bar

Wheel Balancer Specifications



Model	Wheel cover	Cones	Shaft	Laser	A	D	B
WB10	Yes	4 sizes	40mm	No	Man	Man	Man
WB20	Yes	4 sizes	40mm	Yes Alu5 (opt 5)	Auto + Man	Auto + Man	Man
WB30	Yes	4 sizes	40mm	Yes Alu5 (opt 5)	Auto + Man	Auto + Man	Auto + Man

Feature	WB10	WB20	WB30
Distance to wheel	Manual	Automatic	Automatic
Rim diameter	Manual	Automatic	Automatic
Rim width	Manual	Manual	Automatic
Laser for opt5		✓	✓
lock wheel to add weight			✓
Max wheel width	10-24"	10-24"	10-24"
Max wheel diam	47"	47"	47"
Max wheel weight	65kg	65kg	65kg
Cones	4	4	4
Quick nut	✓	✓	✓
Weight tool	✓	✓	✓
Width scissor	✓	✓	✓
Power supply	240V - 10A	240V - 10A	240V - 10A